



Furukawa - 0614141S - Batería Furukawa FTZ14-S Precargada

V

AH

CCA

POLARIDAD

SALIDA GASES

L

AN

ALT

12

11,8

230

Izquierda

150

87

110

Esta batería se presenta totalmente sellada y precargada, lista para ser instalada y sin la necesidad de añadir ácido.

Prácticamente sin posibilidad de pérdidas de ácido

Reduce al mínimo el proceso de sulfatación

Ideal para motocicletas, ATV, motos de agua...

Ofrece un óptimo "Cold Cranking" (CCA)

NOTA: En caso de almacenaje prolongado revisar la tensión y recargar si es necesario, aconsejamos revisarlas en un plazo de 3-4 meses.



CAUTION: DO NOT OPEN TOP COVER
EXPOSED TO ACID BATTERY
CAUTION: DO NOT OPEN TOP COVER
EXPOSED TO ACID BATTERY
CAUTION: DO NOT OPEN TOP COVER
EXPOSED TO ACID BATTERY

⊕ **FB**

SUPER MF ⊖

FTZ14S

12Volts VALVE REGULATED LEAD ACID BATTERY

充電方法 CHARGING METHOD
標準 STD 1.1A X 5 ~ 10 時間(h)
標準 NORMAL
急速 QUICK 5.5A X 1 時間(h)
急速 RAPIDE
注意事項 ELECTROLYTE FILLED NON-SPILLABLE

11.8Ah(20HR) / 230CCA

SIAM FURUKAWA CO., LTD.
MADE IN THAILAND

SAE **PP**
>PP<



Pb



Pb