



Yuasa - 0614141Y - Batería Yuasa YTZ14-S Precargada

Voltaje: 12V - Amperaje: 11,2Ah. Se suministra con ácido incluido y precargada. Batería hermética precargada

V

AH

CCA

POLARIDAD

SALIDA GASES

L

AN

ALT

12

11,2

230A

Izquierda

150

87

Esta batería se presenta totalmente sellada y precargada, lista para ser instalada y sin la necesidad de añadir ácido.

Prácticamente sin posibilidad de pérdidas de ácido

Reduce al mínimo el proceso de sulfatación

Ideal para motocicletas, ATV, motos de agua...

Ofrece un óptimo "Cold Cranking" (CCA)

NOTA: Caso de almacenaje prolongado revisar la tensión y recargar si es necesario, aconsejamos revisarlas en un plazo de 3-4 meses.

RJ0548

CAUTION: Do not touch the terminals or the battery case with bare hands. If you do, you may get a shock. If you get a shock, stop using the battery immediately. If you are not sure, consult your dealer or the manufacturer.



MF

YUASA

NON-SPILLABLE



YTZ14S

注液済み ELECTROLYTE FILLED
11.8 Ah(20HR)
/230 CCA

12V 11.2Ah(10HR)

充電方法 CHARGING METHOD
METHODE DE CHARGE

標準 Standard : 1.1A×5~10時間(h)
Normal
急速 Quick : 5.5A×1時間(h)
Rapide

SAE PP)PP<



Pb



Pb

MADE IN JAPAN